

SAP BusinessObjects Business Intelligence Suite
Document Version: 4.2 Support Package 3 – 2016-10-03

Patch 3.x Update Guide

Content

1	Document History	3
2	Introduction	4
2.1	About this Document	4
	Constraints	4
	Variables	4
	Terminology	5
3	Planning	7
3.1	Downloading the update packages	7
3.2	Platform support	8
3.3	Patch language support	9
3.4	Prerequisites	9
3.5	Limitations and restrictions	10
3.6	Checking the installed version	11
4	Installation scenarios	12
4.1	Applying the update to a system with multiple SAP BusinessObjects products	12
4.2	Updating web applications	12
4.3	Parallel update	12
4.4	Saving web.xml file modifications	14
5	Update installation on Windows	15
5.1	To install the BI platform server update on Windows	15
5.2	To install client product updates on Windows	16
5.3	Silent installation on Windows	17
	To run a silent installation using a response file on Windows	17
5.4	To uninstall updates on Windows	19
6	Update installation on UNIX	21
6.1	To install the BI platform server update on UNIX	21
6.2	Silent installation on UNIX	23
	To run a silent installation using a response file on UNIX	23
6.3	To uninstall updates on UNIX	24

1 Document History

The following table provides an overview of important document changes.

Version	Date	Description
BI platform Patch 1.x	December, 2015	First release of this document.
BI platform Patch 2.x	April, 2016	Added information about New License Key Requirement in To install the BI platform server update on Windows [page 15] , To install the BI platform server update on UNIX [page 21] , To run a silent installation using a response file on Windows [page 17] , and To run a silent installation using a response file on UNIX [page 23]
BI platform Patch 3.x	September, 2016	Updated the document branding for the Business Intelligence platform Support Package 3 (SP3). Modified the document introduction <i>About this Document</i> .

2 Introduction

2.1 About this Document

This document is intended for the system administrator or IT professional who is responsible for the installation and maintenance of SAP BusinessObjects Business Intelligence Suite products.

Table 1: Selecting the correct guide for your update

Type of update	Guide available on http://help.sap.com/bobip
Updating the BI Suite with the most recent minor release such as installing 4.2 on a 4.0 or 4.1 release.	<i>BI Platform Minor Release Update Guide</i>
Updating your current installation with a new Support package	<i>Support Package Update Guide</i>
Updating 4.2 SP3 version of the BI platform with the last available patch	<i>Patch 3.x Update Guide</i>

You can install the latest version of 4.2 directly on top of a 4.0 or a 4.1 release. The following diagram illustrates the update process:



2.1.1 Constraints

This guide does not describe how to set up a host operating system, supported database, web application server, or web server. If you are planning to use a dedicated database, web application server, or web server, it must be installed and functioning before the BI platform can be installed. Refer to the vendor documentation for more information on installing or upgrading these components.

2.1.2 Variables

The following variables are used throughout this guide.

Variable	Description
<INSTALLDIR>	<p>The directory where the BI Suite is installed.</p> <p>On a Windows machine, the default directory is C : \Program Files (x86)\SAP BusinessObjects\</p>

2.1.3 Terminology

The following terms are used throughout the BI platform documentation:

Table 2:

Term	Definition
add-on products	Products that work with the BI platform but have their own installation program, such as SAP BusinessObjects Explorer
Auditing Data Store (ADS)	The database used to store auditing data
BI platform	An abbreviation for the SAP BusinessObjects Business Intelligence platform
bundled database; bundled web application server	The database or web application server shipped with the BI platform
cluster (noun)	Two or more Central Management Servers (CMSs) working together and using a single CMS database
cluster (verb)	<p>To create a cluster.</p> <p>For example, to create a cluster:</p> <ol style="list-style-type: none"> 1. Install a CMS and CMS database on machine A. 2. Install a CMS on machine B. 3. Point the CMS on machine B to the CMS database on machine A.
cluster key	<p>Used to decrypt the keys in the CMS database.</p> <p>You can change the cluster key in the CCM, but you cannot reset the key like a password. It contains encrypted content and is important not to lose.</p>
CMS	An abbreviation for the Central Management Server
CMS database	The database used by the CMS to store information about the BI platform
deployment	The BI platform software installed, configured, and running on one or more machines

Term	Definition
installation	An instance of BI platform files created by the installation program on a machine
machine	The computer on which the BI platform software is installed
major release	A full release of the software, such as 4.0
migration	<p>The process of transferring BI content from a previous major release (for example, from XI 3.1), using the upgrade management tool.</p> <p>This term does not apply to deployments with the same major release. See promotion.</p>
minor release	A release of some components of the software, such as 4.2
node	A group of BI platform servers that run on the same machine and are managed by the same Server Intelligence Agent (SIA)
Patch	A small update for a specific Support Package version
promotion	The process of transferring BI content between deployments with the same major release (for example, 4.0 to 4.0), using the promotion management application
server	A BI platform process. A server hosts one or more services.
Server Intelligence Agent (SIA)	A process that manages a group of servers, including stopping, starting, and restarting servers
Support Package	A software update for a minor or major release
web application server	A server that processes dynamic content. For example, the bundled web application server for 4.2 is Tomcat 8.
upgrade	The planning, preparation, migration, and post-processes required to complete a migration process

3 Planning

3.1 Downloading the update packages

A separate update package is available for each BI Suite product that has a separate full installation program. See the tables in the steps below to identify the correct package for your product.

1. Go to <https://support.sap.com/home.html> > *Download Software*.
2. In the *Download Software* tab, select *Support Packages and Patches*.
3. In the *Support Packages and Patches* tab, select *A–Z Index*
4. Navigate to your product as follows:

Update package	Path
SAP BusinessObjects Business Intelligence platform servers [1]	► B ► SBOP BI platform (former SBOP Enterprise) ► SBOP BI PLATFORM (ENTERPRISE) ► SBOP BI PLATFORM 4.2 ► SBOP BI PLATFORM SERVERS 4.2 ►
SAP BusinessObjects Business Intelligence platform Client Tools [1] [2]	► B ► SBOP BI platform (former SBOP Enterprise) ► SBOP BI PLATFORM (ENTERPRISE) ► SBOP BI PLATFORM 4.2 ► SBOP BI PLATFORM CLIENTS 4.2 ►
SAP Crystal Reports 2016	► C ► CRYSTAL REPORTS ► SAP CRYSTAL REPORTS 2016 ► SAP CRYSTAL REPORTS 2016 ► [1]
SAP Crystal Reports for Enterprise	► B ► SBOP BI platform (former SBOP Enterprise) ► SBOP BI PLATFORM (ENTERPRISE) ► SBOP BI PLATFORM 4.2 ► CR FOR ENTERPRISE 4.2 ►
SAP BusinessObjects Live Office	► B ► SBOP BI platform (former SBOP Enterprise) ► SBOP BI PLATFORM (ENTERPRISE) ► SBOP BI PLATFORM 4.2 ► SBOP LIVE OFFICE 4.2 ►
SAP BusinessObjects Dashboards	► D ► SBOP DASHBOARDS (XCELSIUS) ► SBOP DASHBOARDS 4.2 ► SBOP DASHBOARDS 4.2 ►
SAP BusinessObjects Explorer	► E ► SBOP EXPLORER ► SBOP EXPLORER 4.2 ► SBOP EXPLORER 4.2 ►

- [1] This update package is also intended for SAP BusinessObjects Edge Business Intelligence.
- [2] Client Tools includes:
 - Web Intelligence Rich Client
 - Business View Manager
 - Report Conversion Tool
 - Web Services query Tool

- Universe Design Tool
- Query as a Web Service
- Information Design Tool
- Translation Management Tool
- Data Federation Administration Tool
- Widgets for SAP BusinessObjects Business Intelligence platform
- Developer Components:
 - SAP BusinessObjects BI platform Java SDK
 - SAP BusinessObjects BI platform Web Services SDK
 - SAP BusinessObjects BI platform .NET SDK
 - SAP Crystal Reports Java SDK
 - SAP BusinessObjects Semantic Layer Java SDK

5. Select your platform.

6. Select your update package then follow the instructions on the website to download and extract the package.

The Patch version is listed in the [title](#) column.

The software may take a long time to download, and you may need to contact the system administrator to ensure your company's firewall will not terminate the download process.

3.2 Platform support

The following table shows the platform support for each update package.

Update Package	Windows	AIX	Solaris	Linux
SAP BusinessObjects Business Intelligence platform servers	✓	✓	✓	✓
SAP BusinessObjects Business Intelligence platform Client Tools	✓			
SAP Crystal Reports 2016	✓			
SAP Crystal Reports for Enterprise	✓			
SAP BusinessObjects Live Office	✓			
SAP BusinessObjects Dashboards	✓			
SAP BusinessObjects Explorer	✓	✓	✓	✓

3.3 Patch language support

A Patch only contains string resources for English, and any string fix resolutions contained in the Patch will be displayed in English. Translations for string fixes are added to the next available Support Package containing the fix.


3.4 Prerequisites

Before applying an update to your system the following planning steps are recommended:

- If you are updating from a 4.0 or 4.1 deployment to a 4.2 deployment, we recommend that you back up your CMS database. Uninstalling the 4.2 update does not restore the 4.0 or 4.1 database: it must be restored manually. See the *SAP BusinessObjects Business Intelligence Platform Administrator Guide*.
- Back up your existing BI Suite deployment. For details on backing up your deployment see the *SAP BusinessObjects Business Intelligence Platform Administrator Guide*.

Note

If you are using IBM DB2 for the BI platform CMS, we recommend that you back up the CMS database before running the 4.2 update installation program. To avoid CMS database corruption, ensure that during the update installation process the CMS database is up and running and that the update process is not interrupted.

- Make sure all parts of your BI Suite deployment, including any add-on products you have installed, are compatible with the version of the BI platform that you are updating to. This information can be found in the Product Availability Matrix, available at <https://support.sap.com/release-upgrade-maintenance/pam.html> .
- Review the *Release Restrictions* document for important issues, limitations, and works-arounds for the release.
- Review the *Fixed Issues* document to determine if defects addressed by the update are relevant to your deployment.
- Review [Limitations and restrictions \[page 10\]](#).
- To enable SAP BW design time improvements, see in *SAP Support for BW* in the *Business Intelligence Platform Installation Guide*.
- Identify all SAP BusinessObjects products and components that require updates. Updates are provided for each product that has its own installation program. Refer to [Downloading the update packages \[page 7\]](#) to identify the updates required.
 - On Windows, installed updates can be determined from the Windows *Add/Remove Programs* list.
 - On Unix, installed updates can be determined by running `<INSTALLDIR>/modifyOrRemoveProduct.sh`
- Review the “Installation scenarios” section in this guide.

3.5 Limitations and restrictions

The following limitations and restrictions apply to update installations:

- Updates are maintenance installations, not complete product installations. An SAP BusinessObjects product must be installed in order to install a update.
- Updates can only be installed in their entirety. You cannot install a subset of updates.
- Updates only update features that are already installed. For example:
 - If the full installation that you are updating is a custom installation, the update installation will only update the subset of files that were originally installed.
 - If new features were introduced in a release, they will not be installed by the update installation program. You must do a modify installation to get the new features. For information on how to do a modify installation, see *To modify SAP BusinessObjects Business Intelligence platform* in the *Business Intelligence Platform Installation Guide*.
- Updates only apply fixes for language packs that are already installed. If you want to install a language that was introduced in an update, you will need to modify installation.
- It is required that all products in an SAP BusinessObjects Suite deployment be at the same maintenance level.
 - If you update one SAP BusinessObjects product in the deployment, you must also update all other products.
 - If you uninstall an update for one SAP BusinessObjects product in your deployment, you must uninstall the same update for all products.
 - If you install a new SAP BusinessObjects product, apply all updates to the new product until it is at the same version as all other products in the deployment.
- Patches are designed for a specific Support Package level. For example, a Patch designed for Support Package 5 cannot be installed if your software is at only the Support Package 4 level. You must upgrade to the Support Package 5 level before installing that Patch.
- Patches designed for the same Support Package level are cumulative. Therefore, it is unnecessary to install an earlier Patch from the same Support Package level.
- The update installation program can automatically redeploy BI platform web applications to the bundled Tomcat web application server. If you are using a different web application server, you must use WDeploy to redeploy those applications after installing the update.
For more information, see [Updating web applications \[page 12\]](#).
- You must create a response file with the same installation program that you will use to run it. You cannot re-use a response file from a previous release, or between full installation and an update installation.
For more information, see [To run a silent installation using a response file on Windows \[page 17\]](#) or [To run a silent installation using a response file on UNIX \[page 23\]](#)
- This installation program will not update SAP BusinessObjects Design Studio BI platform add-on. If you are updating a 4.0 or 4.1 release to a 4.2 release, Design Studio will not work. You need to install the Design Studio BI platform add-on as described in the SAP Note 1760372 <http://service.sap.com/notes>.
- Web Intelligence in BI 4.2 contains corrections not included in previous versions of XI 2.x, XI 3.x, XI3.1.x BI4.0.x, and BI4.1.x . Web Intelligence documents migrated from XI 3.X or BI 4.0 to BI 4.1 Support Package 03 may display different results. For more details on potential differences, refer to the white paper at <http://scn.sap.com/docs/DOC-39973>.

3.6 Checking the installed version

Use one of the following methods to check the version of the BI platform that you have installed:

- On Windows deployments, use Windows Add Remove Programs (ARP)
- On Unix or Linux deployments, run `modifyOrRemoveProducts.sh`

BI products and Client Tools

You can see the current version information for BI platform Client Tools and other SAP BusinessObjects BI products such as SAP Crystal Reports in the ► [Help](#) ► [About](#) ► menu.

4 Installation scenarios

4.1 Applying the update to a system with multiple SAP BusinessObjects products

Due to product interdependencies, it is required that all SAP BusinessObjects products be at the same maintenance level. For example, if you want to apply an update to SAP Crystal Reports in a deployment where you also have SAP BusinessObjects Live Office and the BI platform installed, you must apply three separate updates for all three products so that all products are running at the same maintenance level.

4.2 Updating web applications

How you update the BI platform web applications depends on what type of web application server you are using:

- If you are using the bundled Tomcat web application server, the BI platform WAR files are automatically updated using the update installation program. No additional steps are required.
- If you are not using the bundled Tomcat web application server, use the update installation program to install the new WAR files to `<INSTALLDIR>/enterprise_xi40/warfiles/webapps`, then use WDeploy to deploy the WAR files to your web application server. If you are installing multiple updates, install all updates first to obtain a final set of WAR files that can be redeployed once. See *SAP BusinessObjects Business Intelligence Platform Web Application Deployment Guide* for instructions on using WDeploy.

Note

You must update all the BI platform WAR files in your deployment. It is required that all BI suite components, including web applications, be at the same version.

4.3 Parallel update

The parallel update feature was introduced in 4.0 SP5. It allows you to run the update installation on multiple machines at the same time, significantly decreasing the time required to update a distributed deployment. You no longer have to update one machine at a time.

To perform a parallel update to a distributed deployment, install the updates in the following order:


1. Run the update installation on all CMS host machines, in parallel (at the same time).
 - Wait for all machines to finish updating before going to the next step.

- Wait until the update installation has finished running on all CMS machines before you restart any CMS machine. Even if the update installation program requests a restart, do not restart the machine until all CMS machines have finished updating.
2. Ensure at least one CMS machine is running and available before you start updating the non-CMS machines.
3. Run the update installation on all non-CMS machines, in parallel.
 - When prompted to log on to a CMS, use the CMS machine from step 2.
 - Wait for all machines to finish updating before going to the next step.
4. Once the update has finished installing on all non-CMS machines, restart all the CMS machines.

Repeat this process for every product in the deployment. For example, BI platform, Explorer and Client Tools. If a product is only installed on non-CMS machines, steps 1 and 2 can be skipped.

i Note

- There must be at least one CMS machine available to the non-CMS machines that you are updating.
- All CMS machines that are running when you begin updating, and any additional CMS machines that start during the update, must be available for the duration of the update.
- You should not run any additional installation, maintenance, or server administration workflows that could cause the CMS machines to restart while the update is taking place.



4.4 Saving web.xml file modifications

When you install an update, the `web.xml` files for web applications that have been deployed to a web application server are overwritten. This means that any customizations that you've made by changing the `web.xml` files on the web application server are lost after applying an update.

If you modified a `web.xml` file for a web application and do not want to lose your modifications, you must make the modifications in the BI platform installation directory. Changes made to the configuration files in the BI platform installation directory will be retained when patching.

On Windows systems, this directory is:

```
<INSTALLDIR>\SAP BusinessObjects Enterprise XI 4.0\warfiles\webapps.
```

On UNIX systems, this directory is:

```
<INSTALLDIR>/sap_bobj/enterprise_xi40/warfiles/webapps.
```

After you've applied the update, rebuild the affected `.war` files and redeploy the `.war` files to the web application server.

5 Update installation on Windows

You must have Administrator privileges on your Windows machine to run an update installation.

In order to free resources on the machine on which you are installing this update, it is recommended that you use the Central Management Console (CMC) to stop all of the BI platform servers on the machine before installing the update, with the following exceptions:

- Server Intelligence Agent (SIA)
- Central Management Server (CMS)
- Input and Output File Repository Servers (FRS)
- CMS system database

These services and servers must be running for the installation to proceed.


If you are updating a product that contains server components, you must provide the CMS logon credentials. This is required to update content that is stored in the CMS database, such as localized strings for server properties.

Note

The installation cannot proceed if Secure Sockets Layer (SSL) is enabled. If SSL is enabled on the machine where you are installing the update, you must turn it off before doing the installation. Turn SSL back on after the installation is finished.

5.1 To install the BI platform server update on Windows

1. Launch the installation by running `setup.exe`.
The installation program starts the prerequisite checks to ensure the BI platform update can be installed to your machine.
2. On the [Check Prerequisites](#) window, review the results of the prerequisite checks. If you desire to continue the installation, choose [Next](#).
3. In the [Installation wizard](#) window, review the instructions displayed and choose [Next](#).
4. In the [License Agreement](#) window, review the contents of the End User License Agreement, and accept the license agreement, and choose [Next](#).
5. In the [New License Key Requirement](#) window, review the contents of the New License Requirement, and select the check box, and choose [Next](#).

When you update from SAP BusinessObjects Business Intelligence Platform 4.2 SP2 or earlier versions to SAP BusinessObjects Business Intelligence Platform 4.2 SP3 or higher versions, the existing licenses behave as invalid licenses. You need to request a new license key for SAP BusinessObjects Business Intelligence Platform 4.2 update from SAP Service Market Place, visit <https://support.sap.com/keys-systems-installations/keys.html> 

For more information on how to request a new license key, visit <http://scn.sap.com/docs/DOC-70095> 

After you update your system to SAP BusinessObjects Business Intelligence Platform 4.2 update, you must logon to Central Management Console; delete the old license key and add the new license key. Alternatively, you can run the script to delete the license keys. For more information on how to delete the license key through the script, see SAP Note [2276413](#).

i Note

Until you add the new license key in Central Management Console, certain servers are in disabled state.

For more information, see **Business Intelligence Platform Administrator Guide**

6. If the update includes server components, the *Existing CMS Deployment Information* window is displayed. Type the Hostname, Port Number, and Administrator Password for your deployment's CMS, and click *Next*.
7. In the *Select Installation Mode* window, choose the *Standard Installation* radio button
8. In the *Web Application Deployment* window, choose the suitable web application deployment radio button.

i Note

If default Tomcat JAVA Web Application Server is present in the base installation, Business Intelligence Platform installer prompts the *Web Application Deployment* window. Else, the installer does not prompt *Web Application Deployment* window.

- Choosing the *Deploy web applications now* radio button deploys the web application contents on the default Tomcat JAVA web application server.
 - Choosing the *Deploy web application later* radio button does not deploy the web application contents on the default Tomcat JAVA web application server.
 - We recommend you to choose the *Deploy web application later* radio button when you are installing BI platform and other client products. When you are installing the last client product in your system, choose the *Deploy web application now* radio button. This way you can experience overall reduction in system downtime.
9. In the *Start Installation* window, choose *Next* to begin the installation.
The update installation begins. When the installation is complete, a completion screen appears. This screen contains post-installation instructions.

i Note

If web applications are updated as part of the update, depending on the options you chose when you originally installed the BI platform a post installation dialog box may appear with additional instructions for redeploying your .war files.

10. Choose *Finish*.

5.2 To install client product updates on Windows

This procedure is used to install updates to the BI platform Client Tools running on Windows.

Caution

The Client Tools update overwrites the `InformationDesignTool.ini` and `TransMgr.ini` files. If you have customized these .ini files, it is recommended that you save a copy in another directory before starting the installation.

1. Launch the installation by running `setup.exe`
2. Click [Next](#).
3. In the [Welcome](#) dialog box, click [Next](#) to proceed.
4. In the [License Agreement](#) dialog box, review the contents of the End User License Agreement, and click [Next](#) to proceed if you agree to the terms.
If the update includes server components, the [CMS](#) dialog box is displayed.
5. Type the Hostname, Port Number, and Administrator Password for your deployment's CMS, and click [Next](#) to continue.
6. In the [Start Installation](#) dialog box, click [Next](#) to begin the installation.
The update will install. When the installation is complete, a completion screen will appear. This screen may contain some post-installation instructions.
7. Click [Finish](#).

5.3 Silent installation on Windows

5.3.1 To run a silent installation using a response file on Windows

Updates can be installed silently using a response file.

Silent installation is particularly useful when you need to quickly perform multiple installations or automate installations.

To run a silent installation using a response file you must first create a .ini file using the setup program. Once you have created the .ini file, you can run a silent installation by running the `setup.exe` command and specifying the path to the .ini file.

Note

If you are performing a silent installation using a response file, you must create the response file with the `setup.exe` file from the target update or patch installation package. Response files cannot be shared between refresh installations, update installations or patch installations.

1. Create an installation .ini file (a response file).
 - a. Open a command line console.
 - b. From the directory that contains the SAP BusinessObjects `setup.exe` file, run the `setup.exe` command with the write option (`-w`) specified:

```
setup.exe -w <responsefilepath\filename.ini>
```

where `<filename.ini>` is the name you have given to the response file and `<responsefilepath>` is the location where you want the file created.

Note

If a file path is not specified, the file is stored in the directory that `setup.exe` is run from. The installation program must have write permissions on this directory.

- c. Press **Enter** to launch the installation program.
- d. Follow the on-screen instructions to enter your preferred installation settings until you reach the **Start installation** dialog box.
- e. Click **Next**.
The installation program will quit automatically. All parameters from the installation, both user defined and default, are recorded in the `.ini` file which is saved to the directory you specified.

Note


When creating a response file with the GUI installation program, the license key and all passwords entered via the GUI are not written to the response file in plain text format. You must replace the starred entries (*****) with your passwords before performing a silent installation.


2. Edit the response file to replace any starred entries with the appropriate password.
3. Use the following command to run the silent installation using the `.ini` file:

```
setup.exe -r <responsefilepath\filename.ini>.ini
```

The installation log files are saved to `<INSTALLDIR>\InstallData\logs\<DATEandTIME>\`.

Note

When you update from SAP BusinessObjects Business Intelligence Platform 4.2 SP2 or earlier versions to SAP BusinessObjects Business Intelligence Platform 4.2 SP3 or higher versions, the existing licenses behave as invalid licenses. You need to request a new license key for SAP BusinessObjects Business Intelligence Platform 4.2 update from SAP Service Market Place, visit <https://support.sap.com/keys-systems-installations/keys.html> 

For more information on how to request a new license key, visit <http://scn.sap.com/docs/DOC-70095> 

After you update your system to SAP businessObjects Business Intelligence Platform 4.2 update, you must logon to Central Management Console and add the new license key.

Until you add the new license key in Central Management Console, certain servers are in disabled state.

For more information, see **Business Intelligence Platform Administrator Guide**

Note

- In the **Web Application Deployment** window, choose the suitable web application deployment radio button
- If default Tomcat JAVA Web Application Server is present in the base installation, Business Intelligence Platform installer prompts the Web Application Deployment window. Else, the installer does not prompt Web Application Deployment window.
 - Choosing the **Deploy web applications now** radio button deploys the web application contents on the default Tomcat JAVA web application server.

- Choosing the [Deploy web applications later](#) radio button does not deploy the web application contents on the default Tomcat JAVA web application server.
- We recommend you to choose the [Deploy web applications later](#) radio button when you are installing BI platform and other client products. When you are installing the last client product in your system, choose the [Deploy web applications now](#) radio button. This way you can experience overall reduction in system downtime.

5.4 To uninstall updates on Windows

Updates can only be uninstalled one at a time, in the reverse order of installation. When you uninstall updates, ensure that all of the products in your deployment are at the same version before using it.

If you installed the bundled version of Tomcat, the WAR files for the update will be automatically uninstalled by the uninstallation program and the previous versions of the WAR files are automatically restored.

If you did not use the bundled web application server, we recommend that you undeploy all BI platform web applications before uninstalling a update. You can undeploy either manually or by using the WDeploy tool.


Note

The uninstallation program will not revert your CMS from a 4.2 deployment to a 4.0 or 4.1 deployment. If you are uninstalling an update for the following products, you must manually restore the CMS database from your backup after the uninstallation has completed:

- BI platform
- Information Platform Services
- SAP Crystal Server
- SAP BusinessObjects Explorer

Note

Prerequisite for uninstalling or downgrading SAP BusinessObjects BI platform 4.2 SP3

- When uninstalling or downgrading SAP BusinessObjects BI Platform from 4.2 SP3 to 4.2 SP2 or lower versions of 4.1 or to 4.0, ensure that you remove the new license key pertaining to BI Platform 4.2 SP3 from CMC
- If you had uninstalled SAP BusinessObjects BI Platform from 4.2 SP3 without removing the new license key, run the script to remove the key. For more information on removing the key through the script, see SAP Note [2276413](#) 

1. In Windows, click [Start](#), point to [Settings](#), and then select [Control Panel](#).
2. Double-click [Add or Remove Programs](#).
3. Highlight the maintenance entry in the list of programs and click [Change/Remove](#).
The [Application Maintenance](#) dialog box appears.
4. Select [Remove](#) and click [Yes](#).
5. Wait while the appropriate files are removed and the necessary configuration is carried out. Click [Finish](#).

After uninstalling the update, you can redeploy the previous version of the WAR files in <INSTALLDIR>\SAP BusinessObjects Enterprise XI 4.0\warfiles to your web application server. All components in your deployment must be at the same version level.

For more information, refer to the WDeploy or manual deployment instructions in the *SAP BusinessObjects Enterprise Web Application Deployment Guide*.

6 Update installation on UNIX

In order to free resources on the machine on which you are installing this update, it is recommended that you use the Central Management Console (CMC) to stop all of the BI platform servers on the machine before installing the update, with the following exceptions:

- Server Intelligence Agent (SIA)
- Central Management Server (CMS)
- Input and Output File Repository Servers (FRS)
- CMS system database

These services and servers must be running for the installation to proceed.

i Note

If you are updating server components, you must provide the CMS logon credentials. This is required to update content that is stored in the CMS database, such as localized strings for server properties.

i Note

The installation cannot proceed if Secure Sockets Layer (SSL) is enabled. If SSL is enabled on the machine where you are installing the update, you must turn it off before doing the installation. Turn SSL back on after the installation is finished.

6.1 To install the BI platform server update on UNIX

1. Launch the installation by running the following command from the directory containing the update installation program:

```
./setup.sh
```
2. On the *Configure Destination Folder* window, enter the installation directory. The update must be installed into the same directory as the full installation. For example, on BI platform installations, this directory contains the script `modifyOrRemoveProducts.sh`.
The installation program starts the prerequisite checks to ensure the BI platform can be installed to your machine.
3. On the *Check Prerequisites* window, review the results of the prerequisite checks. If you desire to continue the installation, press *Enter*.
4. In the *Installation wizard* window, review the instructions displayed and press *Enter*.
5. In the *License Agreement* window, review the contents of the End User License Agreement, and accept the license agreement, and press *Enter*.
6. In the *New License Key Requirement* window, review the contents of the New License Key Requirement, and press *Enter*.

When you update from SAP BusinessObjects Business Intelligence Platform 4.2 SP2 or earlier versions to SAP BusinessObjects Business Intelligence Platform 4.2 SP3 or higher versions, the existing licenses behave as invalid licenses. You need to request a new license key for SAP BusinessObjects Business Intelligence Platform 4.2 update from SAP Service Market Place, visit <https://support.sap.com/keys-systems-installations/keys.html>

For more information on how to request a new license key, visit <http://scn.sap.com/docs/DOC-70095>

After you update your system to SAP businessObjects Business Intelligence Platform 4.2 update, you must logon to Central Management Console; delete the old license key and add the new license key. Alternatively, you can run the script to delete the license keys. For more information on how to delete the license key through the script, see SAP Note [2276413](#)

i Note

Until you add the new license key in Central Management Console, all the services are in disabled state.

For more information, see **Business Intelligence Platform Administrator Guide**

7. If the update includes server components, the *Existing CMS Deployment Information* window is displayed. Enter your CMS Administrator Ppassword and press *Enter*.
8. In the *Select Installation Mode* window, choose the *Standard Installation* option.
9. In the *Web Application Deployment* window, select the suitable web application deployment option.

i Note

If default Tomcat JAVA Web Application Server is present in the base installation, Business Intelligence Platform installer prompts the Web Application Deployment window. Else, the installer does not prompt Web Application Deployment window.

- Choosing the Deploy web applications now radio button deploys the default Tomcat JAVA web application server.
 - Choosing the deploy web application later radio button does not deploy the default Tomcat JAVA web application server.
 - We recommend you to choose the deploy web application later radio button when you are installing BI platform and other client products. When you are installing the last client product in your system, choose the Deploy web application now radio button. This way you can experience overall reduction in system downtime.
10. On the *Start Installation* window, press *Enter* to start the installation.
The progress indicator displays the status of the installation.

A message appears when the installation is complete. This message may also have some post-install instructions.

i Note

If web applications are modified as part of the update, depending on the options you chose when you originally installed the BI platform a post installation screen may appear with additional instructions for redeploying your .war files.

11. Press to complete the installation.

To review details of the installation, you can view the contents of the installation log file located in `<INSTALLDIR>/InstallData/logs/<DATEandTIME>/`.

6.2 Silent installation on UNIX

6.2.1 To run a silent installation using a response file on UNIX

Updates can be installed silently using a response file.

Silent installation is particularly useful when you need to quickly perform multiple installations or automate installations.

To run a silent installation using a response file you must first create a response file.

The following steps describe how to create a response file using the installation program. Once you have created the response file, you can run a silent installation by running the `./setup.sh` command and specifying the path to the response file.


Note

If you are performing a silent installation using a response file, you must create the response file with the `setup.sh` file from the target update or Patch installation package. Response files cannot be shared between update installations and patch installations.

1. Create a response file.
 - a. From the Patch installation source file location, run the `./setup.sh` command with the write option (`-w`) specified:

```
./setup.sh InstallDir=<INSTALLDIR> -w <responsefilepath/filename.ini>
```

where `<INSTALLDIR>` is the BI platform installation directory and `<responsefilepath/filename.ini>` is the path and file name for the response file you are creating.

- b. Press  to launch the installation program.
- c. Follow the on-screen instructions to enter your preferred installation settings until you reach the [Start installation](#) dialog box of the setup program, the press [Enter](#).
The settings are recorded in the response file.

Note

When creating a response file with the GUI installation program, the license key and all passwords entered via the GUI are not written to the response file in plain text format. You must replace the starred entries (*****) with your passwords before performing a silent installation.

2. Edit the response file to replace any starred entries with the appropriate password.
3. Use the following command to run the silent installation using the `.ini` file:


```
./setup.sh InstallDir=<INSTALLDIR> -r <responsefilepath>/filename.ini
```


where `<responsefilepath>/filename.ini` is the path and name of the response file you created.


The installation log files are saved to `<INSTALLDIR>/InstallData/logs/<DATEandTIME>/`.

Note

When you update from SAP BusinessObjects Business Intelligence Platform 4.2 SP2 or earlier versions to SAP BusinessObjects Business Intelligence Platform 4.2 SP3 or higher versions, the existing licenses behaves as

invalid licenses. You need to request a new license key for SAP BusinessObjects Business Intelligence Platform 4.2 update from SAP Service Market Place, visit <https://support.sap.com/keys-systems-installations/keys.html> .

For more information on how to request a new license key, visit <http://scn.sap.com/docs/DOC-70095> .

After you update your system to SAP BusinessObjects Business Intelligence platform 4.2 update, you must logon to Central Management Console; delete the old license key and add the new license key. Alternatively, you can run the script to delete the license keys. For more information on how to delete the license key through the script, see SAP Note [2276413](#) .

Until you add the new license key in Central Management Console, certain servers are in disabled state.

For more information, see **Business Intelligence Platform Administrator Guide**

Note

- In the *Web Application Deployment* window, choose the suitable web application deployment radio button
- If default Tomcat JAVA Web Application Server is present in the base installation, Business Intelligence Platform installer prompts the Web Application Deployment window. Else, the installer does not prompt Web Application Deployment window.
 - Choosing the *Deploy web applications now* radio button deploys the web application contents on the default Tomcat JAVA web application server.
 - Choosing the *Deploy web applications later* radio button does not deploy the web application contents on the default Tomcat JAVA web application server.
 - We recommend you to choose the *Deploy web applications later* radio button when you are installing BI platform and other client products. When you are installing the last client product in your system, choose the *Deploy web applications now* radio button. This way you can experience overall reduction in system downtime.

6.3 To uninstall updates on UNIX

Updates can only be uninstalled one at a time, in the reverse order of installation. When uninstalling updates, ensure that all of the products in your deployment are at the same version before using it.

If you installed the WAR files to the bundled version of Tomcat, they are automatically uninstalled by the uninstallation program and the previous versions of the WAR files are automatically restored.

If you did not use the bundled web application server, we recommend that you undeploy all BI platform web applications before uninstalling a update. You can undeploy either manually or by using the WDeploy tool.

Note


The uninstallation program will not revert your CMS from a 4.2 deployment to a 4.0 or 4.1 deployment. If you are uninstalling an update for the following products, you must manually restore the CMS database from your backup after the uninstallation has completed:

- BI platform
- Information Platform Services

- SAP Crystal Server
- SAP BusinessObjects Explorer

i Note

Prerequisite for uninstalling or downgrading SAP BusinessObjects BI platform 4.2 SP3

- When uninstalling or downgrading SAP BusinessObjects BI Platform from 4.2 SP3 to 4.2 SP2 or 4.1 or 4.0, ensure that you remove the new license key pertaining to BI Platform 4.2 SP3 from the CMC
- If you had uninstalled SAP BusinessObjects BI Platform from 4.2 SP3 without removing the new license key, run the script to remove the key. For more information on removing the key through the script, see SAP Note [2276413](#) 

1. To uninstall an update, execute the following command from your BI platform installation director:

```
./modifyOrRemoveProducts.sh
```

The *Add or Remove Programs* dialog box is displayed.

2. Select the update you want to remove and press *Enter*.
You will be prompted for your Central Management Server credentials.
 3. Enter your CMS credentials and press *Enter*.
 4. Select *Uninstall Product* and press *Enter*.
A confirmation dialog box is displayed.
 5. Select *Yes* and press .
- The uninstallation process begins.

After uninstalling the update, you can redeploy the previous version of the WAR files in `<INSTALLDIR>/sap_bobj/enterprise_xi40/warfiles` to your web application server. All components in your deployment must be at the same version level.

In order to revert to a 4.0 or 4.1 installation from a 4.2 update installation, you must restore your 4.0 or 4.1 database from a backup. See the *SAP BusinessObjects Business Intelligence Platform Administrator Guide*.

For more information, refer to the WDeploy or manual deployment instructions in the *Business Intelligence Platform Web Application Deployment Guide*.

Important Disclaimers and Legal Information

Coding Samples

Any software coding and/or code lines / strings ("Code") included in this documentation are only examples and are not intended to be used in a productive system environment. The Code is only intended to better explain and visualize the syntax and phrasing rules of certain coding. SAP does not warrant the correctness and completeness of the Code given herein, and SAP shall not be liable for errors or damages caused by the usage of the Code, unless damages were caused by SAP intentionally or by SAP's gross negligence.

Accessibility


The information contained in the SAP documentation represents SAP's current view of accessibility criteria as of the date of publication; it is in no way intended to be a binding guideline on how to ensure accessibility of software products. SAP in particular disclaims any liability in relation to this document. This disclaimer, however, does not apply in cases of wilful misconduct or gross negligence of SAP. Furthermore, this document does not result in any direct or indirect contractual obligations of SAP.

Gender-Neutral Language

As far as possible, SAP documentation is gender neutral. Depending on the context, the reader is addressed directly with "you", or a gender-neutral noun (such as "sales person" or "working days") is used. If when referring to members of both sexes, however, the third-person singular cannot be avoided or a gender-neutral noun does not exist, SAP reserves the right to use the masculine form of the noun and pronoun. This is to ensure that the documentation remains comprehensible.

Internet Hyperlinks

The SAP documentation may contain hyperlinks to the Internet. These hyperlinks are intended to serve as a hint about where to find related information. SAP does not warrant the availability and correctness of this related information or the ability of this information to serve a particular purpose. SAP shall not be liable for any damages caused by the use of related information unless damages have been caused by SAP's gross negligence or wilful misconduct. All links are categorized for transparency (see: <http://help.sap.com/disclaimer>).





**go.sap.com/registration/
contact.html**

© 2016 SAP SE or an SAP affiliate company. All rights reserved.
No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.
Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.
These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.
SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.
Please see <http://www.sap.com/corporate-en/legal/copyright/index.epx> for additional trademark information and notices.