



PUBLIC

2026-07-15

Configuration Guide (OCP-PB)

Content

1	Configuration of OCP - PB.	3
2	Role Assignments for OCP - PB.	4
3	Service Key.	5
4	OCP – PB Configuration Overview.	6
4.1	Common Settings.	7
	OCP - PB Profile.	7
	Action Codes.	8
	Context Profile.	10
	Data Provider.	12
4.2	Visualization.	12
	Alerts.	13
	Calculated Fields.	13
	Chart Colors.	14
	Column Labels.	15
	Table Colors.	16
4.3	Planning.	17
	Strategy Profile.	17
	Sorting Sequence.	18
4.4	Advanced.	20
	Characteristics.	20
5	Formula Definition.	22

1 Configuration of OCP - PB

This documentation describes the configuration of the consulting solution Optimized Capacity Planning – Planning Board (OCP – PB).

This documentation does not contain the SAP standard settings that are required for production processing.

The screens shown in this configuration guide are only examples of configurations. This does not mean that the delivery of OCP - PB contains the settings shown.

To use the OCP – PB planning board, the following prerequisites must be met:

- OCP – PB has been installed in your system
- The configuration required for production processing, including the organizational structure, has already been created.
- The plant settings for MRP planning have been made.
- The users have been assigned the required roles

2 Role Assignments for OCP - PB

To use OCP – PB, the following roles must be assigned to the respective user:

- SAP_BR_PROD_PLNR (or equivalent role)
- SAP_BR_PRODN_ENG_DISC (or equivalent role)
- SAP_BR_PRODMASTER_SPECIALIST (or equivalent role)


In addition, the user must be assigned the business catalog ZSAPLOM_OCPPB using a separate role to execute the application.

For the authorization to change the settings, the business catalog ZSAPLOM_OCPPB_CUST is also required. Users who do not have this business catalog cannot make any settings.

3 Service Key

A service key is required to use OCP – PB.

The service key is uploaded in the settings menu in the app. You can find the settings menu on the right edge of the app.




Menu for service key

If you have any questions about installing the solution or require a service key, please contact scm-consulting-solutions@sap.com.

4 OCP – PB Configuration Overview

The configuration of OCP – PB is done within the app. There is no separate app for making settings for the application.

The configuration is opened using a button in the sidebar.



Calling the configuration

The following menu options are available:

- [Common Settings \[page 7\]](#)
- [Visualization \[page 12\]](#)
- [Planning \[page 17\]](#)
- [Advanced \[page 20\]](#)

Configuration		
	Common Settings	>
	Visualization	>
	Planning	>
	Advanced	>

Configuration overview

The individual menu options have further subchapters.

→ Remember

Changes to the settings will only take effect the next time you start the app. This means that you have to leave the app and call it again.

4.1 Common Settings

In the menu for the general settings, you find the following subitems:

- [OCP - PB Profile \[page 7\]](#)
- [Action Codes \[page 8\]](#)
- [Context Profile \[page 10\]](#)
- [Data Provider \[page 12\]](#)

4.1.1 OCP - PB Profile

The profile for OCP – PB bundles all settings for calling the app.

Profile								New	
Name	Context Prof.		Sel. from	Sel. to	Multi-Lvl. Mode	Strat. Prof.	Delete	Details	
OCP_PL_P1	OCP_C01		-10	30	1 - Determine supply...	S_DEFAULT			>
OCP_T01	OCP_C01		-12	30	1 - Determine supply...	S_DEFAULT			>

OCP - PB OCP - PB Profile

The following settings are defined on the first level:

- The name of the profile.
- The context profile is used to define which functions are displayed in the app.
- The time period starting from today's date in days for which the data is read. Negative values mean reading in the past.
- The mode for reading the multilevel data. Loading additional low-level codes costs runtime. You have the following options:
 - Do not read multilevel data.
 - Read requirement and stock elements: read direct operations and successors of the orders.
 - Read multi-level hierarchy: Read hierarchies completely.
- The strategy profile for all planning functions to which no separate strategy profile was explicitly assigned

You can delete an entry by choosing the button on the right.

You can use the button on the right edge to access further settings for the profile.

The following information can be maintained there:

- Assignment of message groups. [Alerts \[page 13\]](#)
- Assign characteristic profiles. [Characteristics \[page 20\]](#)
- Assignment Gantt color groups. [Chart Colors \[page 14\]](#)
- A description for the profile in different languages.
- Assignment of field configuration groups. [Column Labels \[page 15\]](#).
- Assignment of work centers: This means that the work centers in the selection can be preset for a profile.

4.1.2 Action Codes

In this menu, you maintain the settings for the functions of the planning table.

A number of standard settings are delivered that should not be changed.

You can use this configuration to create additional functions with customer-specific settings.

Name	Insp. Class	Icon	Op. Param.	Stat. Post.	Delete	Details
S_C000	asaplan_c000b_300	gantt-bars	CHUSPLAN			
S_C001	asaplan_c000b_300	machine	CR000PLAN			
S_BSP						
S_EPMULTI	asaplan_c000b_300	exp-chart	S_EPMULTI			
S_EFPOOL	asaplan_c000b_300	multiple-nd-chart	S_EFPOOL	ST_POOL		
S_EFPOOL	asaplan_c000b_300		S_EFPOOL	ST_POOL		

Overview action codes

DESCRIPTION

ACTION CODE PARAMETERS

Description

Description

New

Language	Text	Delete
D	Fertigungsauftrag anzeigen	
E	Display Production Order	

Action Code Parameters

Action Code Parameters

New

No.	Name	Sign	Op.	Value (from)	Value (to)	Delete
1	SEMOBJ			ProductionOrder	display	
2	PARAM			ProductionOrder	@AUFNR	

Action code details

4.1.2.1 Jumps to other apps

The following preconfigured jumps to other apps are delivered:

- S_CO03: Display of production orders
- S_CR03: Display of the work center
- S_MD04: Requirements/stock list
- S_MD13: Display of planned orders
- S_MM03: Display of material master

Note

Customer-specific jumps can be configured. These are not subject to support. The existing settings can serve as a template for configuring jumps to other apps.

To define a customer-specific jump, please follow the steps below:

1st Level

- Create a new Action Code.
- Enter "zsaplom_ocppb_300" as the class.
- The icon can be chosen freely.
- For the header-level parameter, use "CROSSNAV".
- Leave the field for the strategy profile empty.

2nd Level

- Define a description for the function.
- Fill in parameters for the jump.

For a jump, you need at least 2 parameters: Semantic Object and a parameter for calling the app.

Semantic Object

Enter the semantic object in the value from field.

Enter the action in the value to field.

You can find the Semantic Object and the Action in the Fiori App Library. Filter for S/4Hana Public Cloud. [SAP Fiori Apps Reference Library](#)

There, select the desired app. Under "Implementation Information" -> "Configuration" you will find the values for the "Semantic Object" and the "Semantic Action."

Parameters

Parameters are values that must be provided when calling an application, such as the number of an order.

You can also find the parameters in the Fiori App Library.

Using @FIELDNAME, a parameter value can be filled with a value from the OCP-PB table field.

4.1.2.2 Planning Functions

This chapter describes parameter settings for planning functions:

- Sorted dispatching, S_EPSRT: Parameter SEQ, value from = Technical name of the sorting. [Sorting Sequence \[page 18\]](#)
- Multi-level dispatching, S_EPMULTI: Parameter EARLIEST, value from = X. Dispatching at the earliest possible date. Parameter LATEST, value from = X. Dispatching at the requirement date. The parameters are mutually exclusive.
- Remove pool ID, S_POOLIDRM: Parameter REMOVE, value from = X. Removal of the pool ID.

Related Information

[Action Codes \[page 8\]](#)

4.1.3 Context Profile

Context profiles determine which functions are displayed above the list of operations. [Functions of the Capacity Requirements List](#)

The functions in OCP-PB are action codes. You assign action codes to a context profile. The context profile is then assigned to the OCP-PB overall profile. In this way, action codes can be provided to users. The assigned action codes are then displayed next to each other in the toolbar.

It is possible to create submenus in the toolbar that contain several action codes. To do this, a context menu is inserted in another context menu. A submenu generates a dropdown menu button that can be expanded. In this way, functions can be grouped into one button. This saves space on the toolbar.

1st Level

Context Profile			
Name	Icon	Delete	Details
OCP_C01		 	
OCP_NAV	locate-me	 	
OCP_PL	bbyd-dashboard	 	

Context profile 1st level

The technical name of the context profile is entered on the first level of the context profile. If a context profile is to act as a submenu, the icon for the button is stored.

You can use the delete button to delete the context profile.

2nd Level

On the second level, the action codes are entered.

CONTEXT PROFILE ENTRIES
DESCRIPTION

Context Profile Entries

New

No.	Action Code	Ref. Ctx. Prof.	Sort	Trigger	Sub Menu	Status
0	S_CR03		100		No	
Delete:						
1	S_MD04		200		No	
Delete:						
2	S_MD13		50		No	
Delete:						
3	S_CO03		55		No	
Delete:						
4	S_MM03		20		No	
Delete:						

Description

New

Language	Text	Delete
D	Navigation	
E	Navigation	

Action codes within context profile

The order in which the action codes are displayed can be adjusted via sorting. Sorting is optional. A function can be hidden via the status.

The fields Referenced Context Profile and Submenu are only used for submenus.

The description for the context profile is only necessary if the context profile is used as a sub-profile. The description is then displayed in the function bar next to the icon of the context profile.

Submenus

To integrate submenus into the function bar, context profiles are entered and the switch for the submenu is activated.

CONTEXT PROFILE ENTRIES
DESCRIPTION

Context Profile Entries

No.	Action Code	Ref. Ctx. Prof.	Sort	Trigger	Sub Menu	Status
2		OCP_PL	1	GRIDMEN...	X - Yes	
Delete: 🗑						
3		OCP_NAV	2	GRIDMEN...	X - Yes	
Delete: 🗑						

Description

Language	Text	Delete
D	Standard-Kontextprofil	🗑
E	Default Context Profile	🗑

Maintenance of submenus

4.1.4 Data Provider

Reading the data in the OCP - PB consulting solution is done with the help of data providers. Data providers are ABAP classes.

Currently, there is only a single class for reading the data. This area will be further expanded in future versions of OCP - PB.

4.2 Visualization

This menu summarizes all settings for the display of data.

This menu has the following subchapters:

- [Alerts \[page 13\]](#)
- [Calculated Fields \[page 13\]](#)
- [Chart Colors \[page 14\]](#)
- [Column Labels \[page 15\]](#)

- [Table Colors \[page 16\]](#)

4.2.1 Alerts

In the list of operations, there is a column for alerts. In this column, messages can be displayed that indicate certain constellations in the data.

The rules for generating alerts are defined in this menu item.

1st Level

Alerts						New	
Name	Group	Formula	Severity	Delete	Details		
REQUIR_DAT		@SEND0 > @DEMANDDATE	E - Error		>		
REQUI_END0		@SEND0 EQ @DEMANDDATE	W - Warning		>		

Configuration of alerts level 1

On the first level, the following fields are filled in:

- The technical name of the alert
- An alert group: Alerts that are not assigned to a group are processed for all profiles. Alerts that are assigned to a group are only processed in the profile that has the alert group assigned in the profile. [OCP - PB Profile \[page 7\]](#)
- The formula with which the message is checked. [Formula Definition \[page 22\]](#)
- The severity levels of the message: Success, Information, Warning, or Error.
- An entry can be deleted using the trash can icon.
- Using the button for details, you can jump to the second level of the rules.

2nd Level

On the second level, the message texts can be maintained in different languages.

Alert Text			New	
Language	Text	Delete		
D	Bedarfsttermin			
E	Requirements Date			

Alert text

4.2.2 Calculated Fields

In the list of data, there are 6 user fields.

These fields can be filled with values from calculations.

1st Level

To create a calculation, the following fields are filled in:

- Technical designation of the calculation
- Group: Calculations without group assignment are executed for every profile. Calculations with group assignment are only executed when using profiles that have the group assigned. The calculation group is entered in the profile in the section for field configuration. [OCP - PB Profile \[page 7\]](#)
- User field ID: Number from 1-6 to specify the field number into which the result of the calculation should be written.
- Formula for the calculation. Supported operators: +, -, *, /
- A calculation can be deleted using the button with the trash can.
- With the button on the right side, you can jump to the second level.

Calculated Fields					New	⚙
Name	Group	User field ID	Formula	Delete	Details	
TEST_FIELD		3	@ORDER_QTY * 3			

Example Calculation

2nd Level

Field label

In the second level of maintenance, labels for the respective user field can be maintained in different languages.

⚠ Caution

Each user field should only have one formula assigned to it. It is not possible to display more than one value per field.

4.2.3 Chart Colors

If no colors are stored in Customizing, then the operations in the diagram are colored randomly. A color is randomly assigned per material so that orders for the same material have the same color.

A specific coloring can be predefined via Customizing.

1st Level

On the first level, the following fields are filled in:

- Technical name of the coloring
- Priority: Importance of the coloring. A coloring with higher priority overrides a coloring with lower priority.
- Group: Colorings without group assignment are executed for every profile. Colorings with group assignment are only executed when using profiles that have the group assigned. [OCP - PB Profile \[page 7\]](#)
- Color ID in hexadecimal format. A color code can be generated via the search help.
- Formula for the coloring. [Formula Definition \[page 22\]](#)
- A coloring rule can be deleted using the button with the trash can.
- The button on the right side allows you to jump to the second level.

Chart Colors							New	
Name	Prio.	Group	Color		Formula	Delete	Details	
PB_GREEN	0		#3A8A3A		@MATGR EQ GREEN		>	
PB_RED	0		#EF0000		@MATGR EQ RED		>	
PB_REQUIRE	0		#B00000		@DEMANDDATE EQ @SEND		>	

Maintenance of coloring rules

2nd Level

On the second level, a descriptive text for the coloring rule can be entered in various languages. The text is purely informative. It is not displayed in the application.

Description
New

Language	Text	Delete
D	Grünes Material	
E	Green material	

Labeling of the coloring rule

4.2.4 Column Labels

With this setting, the column headers in the data list can be changed.

1st Level

On the first level, the following fields are maintained:

- Technical name of the entry.
- Group: Entries without group assignment are executed for every profile. Entries with group assignment are only executed when using profiles that have the group assigned. [OCP - PB Profile \[page 7\]](#)
- Field name of the field to be renamed. The field is a selection field and displays all available fields.
- The renaming can be deleted using the button with the trash can.
- With the button on the right side, you can jump to the second level.

Column Labels					New	
Name	Group	Field name	Delete	Details		
MATGRP		MATGR - Material Group		>		

Column labeling level 1

2nd Level

On the second level, the labels of the columns are maintained in different languages.

Label Text

New

Language	Text	Delete
D	Materialgruppe	
E	Material Group	

Column labeling level 2

4.2.5 Table Colors

If no colors are stored in Customizing, then the operations in the list of operations will not be colored.

Coloring can be specified via Customizing.

1st Level

On the first level, the following fields are filled in:

- Technical designation of the coloring
- Priority: Importance of the coloring. A coloring with higher priority overrides a coloring with lower priority.
- Group: Colorings without group assignment are executed for every profile. Colorings with group assignment are only executed when using profiles that have the group assigned. [OCP - PB Profile \[page 7\]](#)
- Color: Due to technical limitations, there is only a small selection of possible colors for the list.
- Formula for the coloring. [Formula Definition \[page 22\]](#)
- Field name: Selection of the field that will be colored if the formula is evaluated positively. If no field is selected, the entire row will be colored.
- The trash can button can be used to delete a coloring rule.
- The button on the right side can be used to jump to the second level.

Table Colors								New	
Name	Prio.	Group	Color	Formula	Field name	Delete	Details		
DISPATCHED	0		GRAY - Gray	@DISPATCHED EQ X	DISPATCHED - Dispatch...				
MATGR_GREE	0		GREEN - Green	@MATGR EQ GREEN	MATGR - Material Group				
MATGR_RED	0		RED - Red	@MATGR EQ RED	MATGR - Material Group				
MATGR_YELL	0		YELLOW - Yellow	@MATGR EQ YELLOW	MATGR - Material Group				
PROORD	0		YELLOW - Yellow	@ORDER_TYPE EQ PROO	AUFNR - Order				

Maintenance of coloring rules for the list

2nd Level

On the second level, a descriptive text for the coloring rule can be entered in various languages. The text is purely informative. It is not displayed in the application.

Description

Description

New

Language	Text	Delete
E	Dispatched operation	
D	Eingeplanter Vorgang	

Labeling of the coloring rule

4.3 Planning

In this menu you will find settings for planning with the app.

- [Strategy Profile \[page 17\]](#)
- [Sorting Sequence \[page 18\]](#)

4.3.1 Strategy Profile

Each dispatching function requires a strategy profile. In the strategy profile, certain settings for dispatching are made.

The standard strategy profile S_DEFAULT is used for all planning functions to which no other strategy profile has been assigned.

The assignment of a strategy profile to the action code is done in the menu for the action codes. [Action Codes \[page 8\]](#)

The maintenance of the strategy profiles is two-tiered.

1st Level

Strategy Profile							New	
Name	Direction	Planning Date	Scope	Insert	Cons. Comp. Avail.	Delete	Details	
ST_EPSORT	FORWARD - Forward	MANUAL - Manual input	FINITE - Finite	Find Slot	No			
ST_POOL	FORWARD - Forward	MANUAL - Manual input	FINITE - Finite	Find Slot	No			
S_DEFAULT	FORWARD - Forward	Default	FINITE - Finite	Find Slot	No			

Strategy profiles

On the first level, the following fields are maintained:

- **Name:** Technical name of the strategy profile
- **Direction of scheduling:** Search forward or backward for the next possible scheduling date.
- **Planning date:** Date used to search for the next available scheduling date. Possible options:
 - **Manual entry:** Manual entry by the user via a pop-up window
 - **Earliest possible:** Find the earliest possible date in the future from the current time.
 - **Current operation date:** Use the date on which the operation is currently already scheduled.

- **Scope of planning:** Finite or infinite planning. In finite planning, operations are scheduled where free capacity is available. In infinite planning, the capacity available at the workstation is not taken into account. Operations are scheduled for the specified date.
- **Insertion:** The operations can search for a free slot or be inserted into the production plan at the desired date. When inserting, the operations being inserted will, if necessary, shift all subsequently scheduled operations. Insertion is only relevant for finite scheduling.
- **Consideration of component availability:** If this function is activated, the logic searches for a time when all components are available. If a component is not available during the entire planning period, scheduling cannot be performed.
- An entry can be deleted using the button with the trash can.
- The button on the right edge can be used to open the maintenance of the second level.

Note

For some fields, you can also select the "Default" option. If "Default" is selected, the planning function behaves as it would in the standard version without passing a strategy profile.

2nd Level

On the second level, a description of the strategy profile can be maintained in various languages.

This description is purely informative and has no further function.

Description		
Description		New Settings
Language	Text	Delete
D	Strategieprofil für Aktionscode S_EPSORT	
E	Strategy Profile for Action Code S_EPSORT	

Description of strategy profiles

4.3.2 Sorting Sequence

In this section, you can define a sorting sequence, which is used by the function for sorted scheduling.

The maintenance is carried out in two levels.

1st Level

Sorting Sequence		
Name	Delete	Details
EXAMPLE01		
MATGROUP		

Sorting sequence 1st level

In the first level, you maintain a technical name for the sorting sequence.

This technical name is passed to the planning function for sorted scheduling via the action code in the parameter named SEQ.

Example action code parameters:

DESCRIPTION **ACTION CODE PARAMETERS**

Description

Description		New	⚙️
Language	Text	Delete	
D	Sortierte Einplanung		
E	Sorted dispatching		

Action Code Parameters

Action Code Parameters							New	⚙️
No.	Name	Sign	Op.	Value (from)	Value (to)	Delete		
1	SEQ			EXAMPLE01				

Example action code for sorted dispatching

You can delete the entry using the button with the trash can. The button on the right side takes you to the details.

2nd Level

In the second level, you can specify a description for the sorting. This is optional. The description is for informational purposes only and has no function.

Description

Description		New	⚙️
Language	Text	Delete	
E	Example Sorting Sequence		

Sorting Fields

Sorting Fields				New	⚙️
No.	Field name	Ascending/Descending	Delete		
1	MATGR - Material Group	Ascending			

Sorting sequence 2nd level

All fields of the list can be maintained for the sorting. You must specify whether the sorting is ascending or descending.

A combination of several fields is possible. Example: Material group and material number.

4.4 Advanced

In this section, additional settings for the planning board can be made.

- [Characteristics \[page 20\]](#)

4.4.1 Characteristics

In this chapter, settings for reading characteristics and characteristic values are configured.

The maintenance is done on two levels.

1st Level

Characteristics Profile		
Name	Delete	Details
MERKMALE01		

Maintenance of characteristic profile 1st level

In the first level, the technical name for a characteristic profile is maintained. This characteristic profile is entered in the overall profile for OCP - PB. [OCP - PB Profile \[page 7\]](#)

With the button featuring the trash can icon, an entry can be deleted again.

With the button on the right edge, you can jump to the detailed maintenance.

2nd Level

CHARACTERISTICS

DESCRIPTION

Characteristics

New

No.	Position	Prio.	Source	Class Type	Class Name
1	1 - Column 1	1	H - Header ...	001 - Material	ZMTH_CLS_1
Characteristic: AVC_CR_COUNTERW... Status: Active Delete:					
2	2 - Column 2	1	H - Header ...	001 - Material	ZMTH_CLS_1
Characteristic: DVH_INTERIOR_COLOR Status: Active Delete:					

Description

New

Language	Text	Delete
No data available		

Maintenance of characteristic profile 2nd level

In the second level, the selection of characteristics for the characteristic profile is maintained.

The following fields are maintained:

- **Number:** Sequential number of the entry
- **Position:** Selection of the position in which the data is displayed. There are always two fields per position: characteristic and characteristic value.
- **Priority:** Priority for reading characteristic values. If multiple entries per position are maintained, a higher priority overrides a lower priority if data is available for both priorities.
- **Source:** Origin of the material number for reading the characteristics.
- **Class type:** Class type for reading characteristics.
- **Class name:** Class name of the characteristic class.
- **Characteristic:** Technical name of the characteristic
- **Status:** Entries can be deactivated; then they are no longer processed.

5 Formula Definition

In various settings menus for OCP-PB, formulas can be stored for evaluation.

The evaluation of formulas can then trigger certain actions, such as coloring or an alert.

In OCP-PB, formulas must be defined in a very specific way.

Formulas must be defined so that their result is either true or false.

Example:

@SENDD > @DEMANDDATE

(The end date of an operation is greater than the required date)

The following rules must be observed:

- All components of the formula must be separated by spaces.
- Field values can be included in the formula using the notation @FIELDNAME (technical field name).
- Supported operators:
 - Arithmetic operators: +, -, *, /, ^
 - Comparison operators: >, <, >=, <=, EQ
 - Logical operators: AND, OR
- Parentheses are supported. There must be spaces before and after the parenthesis.
- Operator priorities are taken into account, but parentheses take precedence over priorities.
- Literal values can be used, but currently only if they do not contain spaces. Examples:
 - @FIELDNAME > 100
 - @FIELDNAME EQ ABC
 - 1 EQ 1 (for a formula that is always true).
- Calculations with date fields are possible. Example: (@DATEFIELD + 7) <= @OTHER_DATEFIELD

⚠ Restriction

- Formulas cannot be applied to the result of another formula, so for example, coloring cannot access the result of calculated field values.
- Action codes cannot access calculated values.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon  : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon  : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2026 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.

